

9901B535-01-G - URACRIL - OPACO ACRILICO 30 GLOSS ACRYLIC TOP COAT 30 GLOSS TRASPARENTE

Safety Data Sheet

According to Canadian HPR - WHMIS 2015

1. Identification

1.1. Product identifier

Code: **9901B535-01-G**
Product name: **URACRIL - OPACO ACRILICO 30 GLOSS ACRYLIC TOP COAT 30 GLOSS TRASPARENTE**

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: **2K acylic finish**

Identified Uses	Industrial	Professional	Consumer
Painting of wood for interior, furnitures and accessories	✓	-	-

1.3. Details of the supplier of the safety data sheet

Name: **ALCEA S.p.A.**
Full address: **Via Piemonte 18**
District and Country: **20030 Senago (MI) Italy**
Tel.: **+39.02-99014-1 (centralino)**
Fax: **+39.02-99014-300**

e-mail address of the competent person responsible for the Safety Data Sheet: **Ufficio Tecnico (msds@alcea.com)**

Supplier: **Ufficio Tecnico (msds@alcea.com)**

1.4. Emergency telephone number

For urgent inquiries refer to: **ALCEA Technical Office Tel. + 39.02-99014-220 / 221 (Monday to Friday 8.00-12.00 / 13.00-17.00)**

CENTRI ANTIVELENI (CAV)
- Osp. Niguarda Ca' Granda
Piazza Ospedale Maggiore, 3 - 20162 - Milano - Tel: 02-66101029

2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in Canada's Hazardous Products Regulations (HPR) (WHMIS 2015). The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Classification and Hazard Statement

Flammable liquid, category 2

Carcinogenicity, category 2

Reproductive toxicity, category 2

Specific target organ toxicity - repeated exposure, category 2

Eye irritation, category 2

Skin irritation, category 2

Skin sensitization, category 1

Specific target organ toxicity - single exposure, category 3

Hazard pictograms:

Highly flammable liquid and vapour.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause damage to organs through prolonged or repeated exposure.

Causes serious eye irritation.

Causes skin irritation.

May cause an allergic skin reaction.

May cause drowsiness or dizziness.



9901B535-01-G - URACRIL - OPACO ACRILICO 30 GLOSS ACRYLIC TOP COAT 30 GLOSS TRASPARENTE

2. Hazards identification ... / >>

Signal words: Danger

Hazard statements:

H225	Highly flammable liquid and vapour.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.

Precautionary statements:

Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust / vapors / aerosols.
P202	Do not handle until all safety precautions have been read and understood.
P242	Use non-sparking tools.
P201	Obtain special instructions before use.
P280	Wear protective gloves/ protective clothing / eye protection / face protection.
P271	Use only outdoors or in a well-ventilated area.
P264	Thoroughly wash the contaminated parts after use with soap and water.
P240	Ground and bond container and receiving equipment.
P243	Take action to prevent static discharges.
P241	Use explosion-proof [electrical / ventilating / lighting / . . .] equipment.
P272	Contaminated work clothing should not be allowed out of the workplace.

Response:

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P312	Call a POISON CENTRE / doctor / . . . if you feel unwell.
P304+P340	IF INHALED: remove person to fresh air and keep comfortable for breathing.
P362+P364	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: use foam, powder or CO2 to extinguish, "do not use water".

Storage:

P403+P235	Store in a well-ventilated place. Keep cool.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

Disposal:

P501	Dispose of the product / container in an ecological platform.
-------------	---

2.2. Other hazards

Environmental classification as for Reg. (EC) 1272/2008 (CLP):

The product is classified as hazardous for environment pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

Classification and Hazard Statement

Hazardous to the aquatic environment, chronic toxicity, category 3

Harmful to aquatic life with long lasting effects.

Hazard statements:

H412	Harmful to aquatic life with long lasting effects.
-------------	--

Precautionary statements:

Prevention:

P273	Avoid release to the environment.
-------------	-----------------------------------

Response:

--

Storage:

--

Disposal:

P501	Dispose of the product / container in an ecological platform.
-------------	---

3. Composition/information on ingredients

9901B535-01-G - URACRIL - OPACO ACRILICO 30 GLOSS ACRYLIC TOP COAT 30 GLOSS TRASPARENTE

3. Composition/information on ingredients ... / >>**3.2. Mixtures**

Contains:

Identification	x = Conc. % (w/w)	Classification:
N-butyl acetate		
N-BUTYL ACETATE		
CAS	123-86-4 $32 \leq x < 34$	Flammable liquid, category 3 H226, Specific target organ toxicity - single exposure, category 3 H336
REACH Reg. 01-2119485493-29-XXXX		
Toluene		
Toluene		
CAS	108-88-3 $17 \leq x < 18$	Flammable liquid, category 2 H225, Reproductive toxicity, category 2 H361, Aspiration hazard, category 1 H304, Specific target organ toxicity - repeated exposure, category 2 H373, Skin irritation, category 2 H315, Specific target organ toxicity - single exposure, category 3 H336
REACH Reg. 01-2119471310-51-XXXX		
ETHYL ACETATE		
ETHYL ACETATE		
CAS	141-78-6 $5 \leq x < 6$	Flammable liquid, category 2 H225, Eye irritation, category 2 H319, Specific target organ toxicity - single exposure, category 3 H336
REACH Reg. 01-2119475103-46-XXXX		
XYLENE (MIXTURE OF ISOMERS)		
XYLENE (MIXTURE OF ISOMERS)		
CAS	1330-20-7 $4.5 \leq x < 5$	Flammable liquid, category 3 H226, Acute toxicity, category 4 H312, Acute toxicity, category 4 H332, Aspiration hazard, category 1 H304, Specific target organ toxicity - repeated exposure, category 2 H373, Eye irritation, category 2 H319, Skin irritation, category 2 H315, Specific target organ toxicity - single exposure, category 3 H335, Hazardous to the aquatic environment, chronic toxicity, category 3 H412
REACH Reg. 01-2119488216-32-XXXX		
METHYL ETHYL KETONE		
2-BUTANONE		
MEK		
BUTANONE		
CAS	78-93-3 $3.5 \leq x < 4$	Flammable liquid, category 2 H225, Eye irritation, category 2 H319, Specific target organ toxicity - single exposure, category 3 H336
REACH Reg. 01-2119457290-43-XXXX		
1-Methoxy-2-propyl acetate		
1-METHOXY-2-PROPYL ACETATE		
PMA		
PROPYLENMETHYLGLYCOL ACETATE		
METHOXY PROPYL ACETATE		
CAS	108-65-6 $1.5 \leq x < 2$	Flammable liquid, category 3 H226, Specific target organ toxicity - single exposure, category 3 H336
REACH Reg. 01-2119475791-29-XXXX		
Isobutyl acetate		
ISOBUTYL ACETATE		
CAS	110-19-0 $1.5 \leq x < 2$	Flammable liquid, category 2 H225
REACH Reg. 01-2119488971-22-XXXX		
2-methylpropan-1-ol		
ISOBUTANOL		
ISOBUTYL ALCOHOL		
CAS	78-83-1 $1.5 \leq x < 2$	Flammable liquid, category 3 H226, Serious eye damage, category 1 H318, Skin irritation, category 2 H315, Specific target organ toxicity - single exposure, category 3 H335, Specific target organ toxicity - single exposure, category 3 H336
REACH Reg. 01-2119484609-23-XXXX		
ETHYLBENZENE		
ETHYLBENZENE		
CAS	100-41-4 $0.4 \leq x < 0.7$	Flammable liquid, category 2 H225, Carcinogenicity, category 2 H351, Acute toxicity, category 4 H332, Aspiration hazard, category 1 H304, Specific target organ toxicity - repeated exposure, category 2 H373
REACH Reg. 01-2119489370-35-XXXX		
BENZOTRIAZOLE DERIVATE MIXTURE		
BENZOTRIAZOLE DERIVATE MIXTURE		
CAS	0.1 $\leq x < 0.4$	Skin sensitization, category 1 H317, Hazardous to the aquatic environment, chronic toxicity, category 2 H411
REACH Reg. 01-0000015075-76-XXXX		
METHYL METHACRYLATE		
METHYL METHACRYLATE		

9901B535-01-G - URACRIL - OPACO ACRILICO 30 GLOSS ACRYLIC TOP COAT 30 GLOSS TRASPARENTE

3. Composition/information on ingredients ... / >>

METIL 2-METILPROP-2-ENOATO

CAS 80-62-6 $0.1 \leq x < 0.4$ **Flammable liquid, category 2 H225, Skin irritation, category 2 H315, Specific target organ toxicity - single exposure, category 3 H335, Skin sensitization, category 1 H317**

REACH Reg. 01-2119452498-28-XXXX

BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL) SEBACATECAS 41556-26-7 $0.1 \leq x < 0.25$ **Skin sensitization, category 1 H317, Hazardous to the aquatic environment, acute toxicity, category 1 H400 M=1, Hazardous to the aquatic environment, chronic toxicity, category 1 H410 M=1**

REACH Reg. 01-2119491304-40-XXXX

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

The full wording of hazard (H) phrases is given in section 16 of the sheet.

4. First-aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately.

INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

5. Fire-fighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

Extinguishing substances are: carbon dioxide, foam, chemical powder. For product loss or leakage that has not caught fire, water spray can be used to disperse flammable vapours and protect those trying to stem the leak.

UNSUITABLE EXTINGUISHING EQUIPMENT

Do not use jets of water. Water is not effective for putting out fires but can be used to cool containers exposed to flames to prevent explosions.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Excess pressure may form in containers exposed to fire at a risk of explosion. Do not breathe combustion products.

METHYL METHACRYLATE

Heat may cause the product to polymerise, which could lead to explosion.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

6. Accidental release measures ... / >>

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

7. Handling and storage**7.1. Precautions for safe handling**

Keep away from heat, sparks and naked flames; do not smoke or use matches or lighters. Without adequate ventilation, vapours may accumulate at ground level and, if ignited, catch fire even at a distance, with the danger of backfire. Avoid bunching of electrostatic charges. When performing transfer operations involving large containers, connect to an earthing system and wear antistatic footwear. Vigorous stirring and flow through the tubes and equipment may cause the formation and accumulation of electrostatic charges. In order to avoid the risk of fires and explosions, never use compressed air when handling. Open containers with caution as they may be pressurised. Do not eat, drink or smoke during use. Avoid leakage of the product into the environment.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Store in a cool and well ventilated place, keep far away from sources of heat, naked flames and sparks and other sources of ignition. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

8. Exposure controls/personal protection**8.1. Control parameters**

Regulatory References:

ONT	Ontario	R.R.O 1990, REGULATION 833
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.
	TLV-ACGIH	ACGIH 2021

XYLENE (MIXTURE OF ISOMERS)**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	434	100	651	150	
ONT	CAN		100		150	
OEL	EU	221	50	442	100	SKIN
OSHA	USA	435	100			

9901B535-01-G - URACRIL - OPACO ACRILICO 30 GLOSS ACRYLIC TOP COAT 30 GLOSS TRASPARENTE

8. Exposure controls/personal protection ... / >>

METHYL METHACRYLATE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	205	50	410	100	
OEL	EU		50		100	
OSHA	USA	410	100			

2-METHOXY-1-METHYLETHYL ACETATE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
OEL	EU	275	50	550	100	SKIN
ONT	CAN	270	50			

2-METHYLPROPAN-1-OL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	152	50			
ONT	CAN	50				
OSHA	USA	300	100			

TOLUENE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-		20			
ONT	CAN		20			
OEL	EU	192	50	384	100	SKIN
OSHA	USA		200		300	

ETHYLBENZENE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	87	20			
ONT	CAN		20			
OEL	EU	442	100	884	200	SKIN
OSHA	USA	435	100			

ETHANOL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-			1884	1000	
ONT	CAN				1000	
OSHA	USA	1900	1000			

2-PROPANOL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	492	200	983	400	
ONT	CAN	200				
OSHA	USA	980	400			

9901B535-01-G - URACRIL - OPACO ACRILICO 30 GLOSS ACRYLIC TOP COAT 30 GLOSS TRASPARENTE

8. Exposure controls/personal protection ... / >>**METHYL ETHYL KETONE****Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	590	200	885	300	
ONT	CAN		200		300	
OEL	EU	600	200	900	300	
OSHA	USA	590	200			

ETHYL ACETATE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	1441	400			
ONT	CAN		400			
OEL	EU	734	200	1468	400	
OSHA	USA	1400	400			

N-BUTYL ACETATE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
OEL	EU	241	50	723	150	
TLV-ACGIH	-		50		150	
ONT	CAN		150		200	
OSHA	USA	710	150			

ISOBUTYL ACETATE**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
OEL	EU	241	50	723	150	
TLV-ACGIH	-		50		150	
ONT	CAN		150			
OSHA	USA	700	150			

2-(2-BUTOXYETHOXY)ETHANOL**Threshold Limit Value**

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV-ACGIH	-	66	10			
OEL	EU	67.5	10	101.2	15	

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).

The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.

The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133, CSA Standard CAN/CSA-Z94.3-92).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134, CSA Standard Z94.4-02). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the

8. Exposure controls/personal protection ... / >>

threshold values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134, CSA Standard Z94.4-02.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

9. Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Properties	Value	Information
Appearance	liquid	
Colour	colourless	
Odour	Aromatic, chetons, esters.	
Odour threshold	not available	
pH	not available	
Melting point / freezing point	not available	
Initial boiling point	85 °C (185 °F)	
Boiling range	not available	
Flash point	< 23 °C (73,4 °F)	
Evaporation rate	not available	
Flammability	not available	
Lower inflammability limit	not available	
Upper inflammability limit	not available	
Lower explosive limit	not available	
Upper explosive limit	not available	
Vapour pressure	not available	
Vapour density	not available	
Relative density	0.946	
Solubility	Partially-Solubility	
Partition coefficient: n-octanol/water	not available	
Auto-ignition temperature	not available	
Decomposition temperature	not available	
Viscosity	>20,5 mm2/sec (40°C)	
Explosive properties	not available	
Oxidising properties	not available	

9.2. Other information

Total solids (250°C / 482°F)	28,71 %
VOC :	71,29 % - 674,40 g/litre

10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

2-METHOXY-1-METHYLETHYL ACETATE

Stable in normal conditions of use and storage.

With the air it may slowly develop peroxides that explode with an increase in temperature.

TOLUENE

Avoid exposure to: light.

METHYL ETHYL KETONE

Reacts with: light metals, strong oxidants. Attacks various types of plastic materials. Decomposes under the effect of heat.

ETHYL ACETATE

Decomposes slowly into acetic acid and ethanol under the effect of light, air and water.

N-BUTYL ACETATE

Decomposes on contact with: water.

ISOBUTYL ACETATE

Decomposes under the effect of heat. Attacks various types of plastic materials.

10.2. Chemical stability

10. Stability and reactivity ... / >>

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

The vapours may also form explosive mixtures with the air.

XYLENE (MIXTURE OF ISOMERS)

Stable in normal conditions of use and storage. Reacts violently with: strong oxidants, strong acids, nitric acid, perchlorates. May form explosive mixtures with: air.

METHYL METHACRYLATE

May polymerise on contact with: ammonia, organic peroxides, persulphates. Risk of explosion on contact with: dibenzoyl peroxide, di-tert-butyl peroxide, propionaldehyde. May react dangerously with: strong oxidising agents. Forms explosive mixtures with: air.

2-METHOXY-1-METHYLETHYL ACETATE

May react violently with: oxidising substances, strong acids, alkaline metals.

TOLUENE

Risk of explosion on contact with: fuming sulphuric acid, nitric acid, silver perchlorate, nitrogen dioxide, non-metal halogenates, acetic acid, organic nitrocompounds. May form explosive mixtures with: air. May react dangerously with: strong oxidising agents, strong acids, sulphur.

ETHYLBENZENE

Reacts violently with: strong oxidants. Attacks various types of plastic materials. May form explosive mixtures with: air.

METHYL ETHYL KETONE

May form peroxides with: air, light, strong oxidising agents. Risk of explosion on contact with: hydrogen peroxide, nitric acid, sulphuric acid. May react dangerously with: oxidising agents, trichloromethane, alkalis. Forms explosive mixtures with: air.

ETHYL ACETATE

Risk of explosion on contact with: alkaline metals, hydrides, oleum. May react violently with: fluorine, strong oxidising agents, chlorosulphuric acid, potassium tert-butoxide. Forms explosive mixtures with: air.

N-BUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents. May react dangerously with: alkaline hydroxides, potassium tert-butoxide. Forms explosive mixtures with: air.

ISOBUTYL ACETATE

Risk of explosion on contact with: strong oxidising agents. May react violently with: alkaline hydroxides, potassium tert-butoxide. Forms explosive mixtures with: air.

10.4. Conditions to avoid

Avoid overheating. Avoid bunching of electrostatic charges. Avoid all sources of ignition.

METHYL METHACRYLATE

Avoid exposure to: heat, UV rays. Avoid contact with: oxidising substances, reducing substances, acids, bases.

METHYL ETHYL KETONE

Avoid exposure to: sources of heat.

ETHYL ACETATE

Avoid exposure to: light, sources of heat, naked flames.

N-BUTYL ACETATE

Avoid exposure to: moisture, sources of heat, naked flames.

ISOBUTYL ACETATE

Avoid exposure to: sources of heat, naked flames.

10.5. Incompatible materials

2-METHOXY-1-METHYLETHYL ACETATE

Incompatible with: oxidising substances, strong acids, alkaline metals.

METHYL ETHYL KETONE

Incompatible with: strong oxidants, inorganic acids, ammonia, copper, chloroform.

ETHYL ACETATE

Incompatible with: acids, bases, strong oxidants, aluminium, nitrates, chlorosulphuric acid. Incompatible materials: plastic materials.

N-BUTYL ACETATE

Incompatible with: water, nitrates, strong oxidants, acids, alkalis, zinc.

ISOBUTYL ACETATE

Incompatible with: strong oxidants, nitrates, strong acids, strong bases.

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

METHYL METHACRYLATE

When heated to decomposition releases: harsh fumes, zinc alloys.

ETHYLBENZENE

May develop: methane, styrene, hydrogen, ethane.

11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on toxicological effects

Metabolism, toxicokinetics, mechanism of action and other information

2-METHOXY-1-METHYLETHYL ACETATE

The main route of entry is the skin, whereas the respiratory route is less important due to the low vapour pressure of the product.

Information on likely routes of exposure

XYLENE (MIXTURE OF ISOMERS)

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air.

2-METHOXY-1-METHYLETHYL ACETATE

WORKERS: inhalation; contact with the skin.

TOLUENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; inhalation of ambient air; contact with the skin of products containing the substance.

ETHYLBENZENE

WORKERS: inhalation; contact with the skin.

POPULATION: ingestion of contaminated food or water; contact with the skin of products containing the substance.

N-BUTYL ACETATE

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

XYLENE (MIXTURE OF ISOMERS)

Toxic effect on the central nervous system (encephalopathy); irritating for the skin, conjunctiva, cornea and respiratory apparatus.

2-METHOXY-1-METHYLETHYL ACETATE

Above 100 ppm causes irritation of the eye, nose and oropharynx mucous membranes. At 1000 ppm, disturbance of equilibrium and severe eye irritation can be noticed. Clinical and biological examinations carried out on exposed volunteers revealed no anomalies. Acetate produces greater skin and eye irritation with direct contact. No chronic effects on humans have been reported (INCR, 2010).

TOLUENE

Toxic effect on the central and peripheral nervous system with encephalopathy and polyneuritis; irritating for the skin, conjunctiva, cornea and respiratory apparatus.

ETHYLBENZENE

As the counterparts of benzene, may have an acute effect on the central nervous system, with depression, narcosis, often preceded by dizziness and associated with headache (Ispesl). Is irritating for skin, conjunctiva and respiratory tract.

N-BUTYL ACETATE

In humans, the substance's vapours cause irritation of the eyes and nose. In the event of repeated exposure, skin irritation, dermatitis (dryness and cracking of the skin) and keratitis appear.

Interactive effects

XYLENE (MIXTURE OF ISOMERS)

Intake of alcohol interferes with the metabolism of the substance, inhibiting it. Ethanol consumption (0.8 g/kg) before a 4-hour exposure to xylene vapours (145 and 280 ppm) causes a 50% reduction in the excretion of methyl hippuric acid, whereas the concentration of xylenes in the blood increases approx. 1.5-2 times. At the same time there is an increase in the secondary side effects of the ethanol. The metabolism of the xylenes is increased by phenobarbital and 3-methyl-colantrene type enzyme inducers. Aspirin and xylenes mutually inhibit their conjugation with the glycine, which results in a decrease in urinary excretion of methyl hippuric acid. Other industrial products can interfere with the metabolism of xylenes.

11. Toxicological information ... / >>**TOLUENE**

Certain drugs and other industrial products can interfere with the metabolism of the toluene.

N-BUTYL ACETATE

A case of acute intoxication been reported involving a 33 year old worker while cleaning a tank with a preparation containing xylenes, butyl acetate and ethylene glycol acetate. The person had irritation of the conjunctiva and upper respiratory tract, drowsiness and motor coordination disorders, which disappeared within 5 hours. The symptoms are attributed to poisoning by mixed xylenes and butyl acetate, with a possible synergistic effect responsible for the neurological effects. Cases of vacuolar keratitis are reported in workers exposed to a mixture of butyl acetate and isobutanol vapours, but with uncertainty concerning the responsibility of a particular solvent (INRC, 2011).

ACUTE TOXICITY**XYLENE (MIXTURE OF ISOMERS)**

LD50 (Oral):	3523 mg/kg Rat
LD50 (Dermal):	4350 mg/kg Rabbit
LC50 (Inhalation vapours):	26 mg/l/4h Rat

2-METHOXY-1-METHYLETHYL ACETATE

LD50 (Oral):	8530 mg/kg Rat
LD50 (Dermal):	> 5000 mg/kg Rat

2-METHYLPROPAN-1-OL

LD50 (Oral):	2460 mg/kg Rat
LD50 (Dermal):	2460 mg/kg Rabbit
LC50 (Inhalation vapours):	19.2 mg/l/4h Rat

TOLUENE

LD50 (Oral):	5580 mg/kg Rat
LD50 (Dermal):	12124 mg/kg Rabbit
LC50 (Inhalation vapours):	28.1 mg/l/4h Rat

ETHYLBENZENE

LD50 (Oral):	3500 mg/kg Rat
LD50 (Dermal):	15354 mg/kg Rabbit
LC50 (Inhalation vapours):	17.2 mg/l/4h Rat

METHYL ETHYL KETONE

LD50 (Oral):	2737 mg/kg Rat
LD50 (Dermal):	6480 mg/kg Rabbit
LC50 (Inhalation vapours):	23.5 mg/l/8h Rat

N-BUTYL ACETATE

LD50 (Oral):	> 6400 mg/kg Rat
LD50 (Dermal):	> 5000 mg/kg Rabbit
LC50 (Inhalation vapours):	21.1 mg/l/4h Rat

BENZOTRIAZOLE DERIVATE MIXTURE

LD50 (Oral):	> 5000 mg/kg Rat
LD50 (Dermal):	> 2000 mg/kg Rat
LC50 (Inhalation mists/powders):	5.8 mg/l/4h Rat

BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL) SEBACATE

LD50 (Dermal):	> 2000 mg/kg
----------------	--------------

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY

9901B535-01-G - URACRIL - OPACO ACRILICO 30 GLOSS ACRYLIC TOP COAT 30 GLOSS TRASPARENTE

11. Toxicological information ... / >>

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Suspected of causing cancer

Carcinogenicity Assessment:

108-88-3	TOLUENE ACGIH:: A4 IARC:3
1330-20-7	XYLENE (MIXTURE OF ISOMERS) ACGIH:: A4 IARC:3
100-41-4	ETHYLBENZENE ACGIH:: A3 IARC:2B
67-63-0	2-PROPANOL IARC:3
80-62-6	METHYL METHACRYLATE ACGIH:: A4 IARC:3
64-17-5	ETHANOL ACGIH:: A3 IARC:1

XYLENE (MIXTURE OF ISOMERS)

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC).
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

TOLUENE

Classified in Group 3 (not classifiable as a human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 1999).
The US Environmental Protection Agency (EPA) affirms that "the data is inadequate for an assessment of the carcinogenic potential".

ETHYLBENZENE

Classified in Group 2B (possible human carcinogen) by the International Agency for Research on Cancer (IARC) - (IARC, 2000).
Classified in Group D (not classifiable as a human carcinogen) by the US Environmental Protection Agency (EPA) - (US EPA file on-line 2014).

REPRODUCTIVE TOXICITY

Suspected of damaging fertility or the unborn child

STOT - SINGLE EXPOSURE

May cause drowsiness or dizziness

STOT - REPEATED EXPOSURE

May cause damage to organs

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class Viscosity: >20,5 mm²/sec (40°C)

12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it have negative effects on aquatic environment.

12.1. Toxicity

9901B535-01-G - URACRIL - OPACO ACRILICO 30 GLOSS ACRYLIC TOP COAT 30 GLOSS TRASPARENTE

12. Ecological information ... / >>

BENZOTRIAZOLE DERIVATE MIXTURE

LC50 - for Fish	2.8 mg/l/96h Oncorhynchus mykiss
EC50 - for Crustacea	4 mg/l/48h Daphnia magna
EC50 - for Algae / Aquatic Plants	> 100 mg/l/72h Pseudokirchneriella subcapitata

BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL) SEBACATE

LC50 - for Fish	0.97 mg/l/96h
EC10 for Algae / Aquatic Plants	0.1 mg/l/72h

12.2. Persistence and degradability

XYLENE (MIXTURE OF ISOMERS)

Solubility in water	100 - 1000 mg/l
Rapidly degradable	

METHYL METHACRYLATE

Solubility in water	15300 mg/l
Rapidly degradable	

2-METHOXY-1-METHYLETHYL ACETATE

Solubility in water	> 10000 mg/l
Rapidly degradable	

2-METHYLPROPAN-1-OL

Solubility in water	1000 - 10000 mg/l
Rapidly degradable	

TOLUENE

Solubility in water	100 - 1000 mg/l
Rapidly degradable	

ETHYLBENZENE

Solubility in water	1000 - 10000 mg/l
Rapidly degradable	

METHYL ETHYL KETONE

Solubility in water	> 10000 mg/l
Rapidly degradable	

ETHYL ACETATE

Solubility in water	> 10000 mg/l
Rapidly degradable	

N-BUTYL ACETATE

Solubility in water	1000 - 10000 mg/l
---------------------	-------------------

ISOBUTYL ACETATE

Solubility in water	1000 - 10000 mg/l
Rapidly degradable	

12. Ecological information ... / >>

BENZOTRIAZOLE DERIVATE MIXTURE
NOT rapidly degradable

12.3. Bioaccumulative potential

XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: n-octanol/water 3.12

BCF 25.9

METHYL METHACRYLATE

Partition coefficient: n-octanol/water 1.38

2-METHOXY-1-METHYLETHYL ACETATE

Partition coefficient: n-octanol/water 1.2

2-METHYLPROPAN-1-OL

Partition coefficient: n-octanol/water 1

TOLUENE

Partition coefficient: n-octanol/water 2.73

BCF 90

ETHYLBENZENE

Partition coefficient: n-octanol/water 3.6

METHYL ETHYL KETONE

Partition coefficient: n-octanol/water 0.3

ETHYL ACETATE

Partition coefficient: n-octanol/water 0.68

BCF 30

N-BUTYL ACETATE

Partition coefficient: n-octanol/water 2.3

BCF 15.3

ISOBUTYL ACETATE

Partition coefficient: n-octanol/water 2.3

BCF 15.3

12.4. Mobility in soil

XYLENE (MIXTURE OF ISOMERS)

Partition coefficient: soil/water 2.73

METHYL METHACRYLATE

Partition coefficient: soil/water 0.94

9901B535-01-G - URACRIL - OPACO ACRILICO 30 GLOSS ACRYLIC TOP COAT 30 GLOSS TRASPARENTE

12. Ecological information ... / >>

2-METHYLPROPAN-1-OL

Partition coefficient: soil/water 0.31

N-BUTYL ACETATE

Partition coefficient: soil/water < 3

12.5. Results of PBT and vPvB assessment

PBT substances contained:

BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDINYL) SEBACATE

12.6. Other adverse effects

Information not available

13. Disposal considerations

13.1. Waste treatment methods

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

14. Transport information

14.1. UN number

ADR / RID, IMDG, IATA: 1263

14.2. UN proper shipping name

ADR / RID: PAINT or PAINT RELATED MATERIAL

IMDG: PAINT or PAINT RELATED MATERIAL

IATA: PAINT or PAINT RELATED MATERIAL

14.3. Transport hazard class(es)

ADR / RID: Class: 3 Label: 3



IMDG: Class: 3 Label: 3



IATA: Class: 3 Label: 3



14.4. Packing group

ADR / RID, IMDG, IATA: II

14.5. Environmental hazards

ADR / RID: NO

IMDG: NO

IATA: NO

9901B535-01-G - URACRIL - OPACO ACRILICO 30 GLOSS ACRYLIC TOP COAT 30 GLOSS TRASPARENTE

14. Transport information ... / >>**14.6. Special precautions for user**

ADR / RID:	HIN - Kemler: 33	Limited Quantities: 5 L	Tunnel restriction code: (D/E)
	Special provision: 163, 367, 640C, 650		
IMDG:	EMS: F-E, S-E	Limited Quantities: 5 L	
IATA:	Cargo:	Maximum quantity: 60 L	Packaging instructions: 364
	Pass.:	Maximum quantity: 5 L	Packaging instructions: 353
	Special provision:	A3, A72, A192	

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Substances subject to the Rotterdam Convention:
None

Canadian Regulatory Information

This product has been classified in accordance with the hazard criteria of the Hazardous Products Regulations (HPR).

Safety Data Sheet according to WHMIS 2015.

Inventory Status of the contained substance/s.

All ingredients are listed in DSL.

Architectural Coatings Regulations SOR/2009-264
Any other varnish.

VOC given in g/litre of product in a ready-to-use condition : 674.40
The coating is to be applied without dilution or thinning.

16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H312	Harmful in contact with skin.
H332	Harmful if inhaled.
H304	May be fatal if swallowed and enters airways.
H373	May cause damage to organs through prolonged or repeated exposure.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H335	May cause respiratory irritation.
H317	May cause an allergic skin reaction.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CLP: Regulation (EC) 1272/2008
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation

16. Other information ... / >>

- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

GENERAL BIBLIOGRAPHY:

- GHS rev. 5
- The Merck Index. 10th Edition
- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

- Hazard Products Regulation (HPR)
- WHMIS 2015
- ONTARIO R.R.O. 1990, Regulation 883 (version July 2016)
- IARC website
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Product classification derives from criteria established by the Canada's Hazardous Products Regulations (HPR) (WHMIS 2015), unless determined otherwise in Section 11 and 12. The data for evaluation of chemical-physical properties are reported in section 9.

Changes to previous review:

The following sections were modified:

01.